

J. v. G. LED 12.20 Flasher



With the innovative J. v. G. LED 12.20 Flasher each module is tested not just once, but five times in one go. From this an average is derived which in turn will ensure that the results are more accurate. And that means, later for the dimensioning all wiring connections can be done much more precisely. The advantage is that the LED variant requires less time to determine these five test results than a common flasher for only one test cycle.

Specification datas

- 1 Light Source: LED pulsed lights (8 pieces)
- 2 Life time of a lamp: 5. 000 000 flash times ; 5 flashes in 2 seconds more flash possible (up to 40).
- 3 Full area intensity: 70 to 120 mW/cm
- 4 Correction: Automatically correct against to temperature and power drift to standard condition.
Also long pulse flash possible to measure thinfilm

Measures the following parameters:

- I-V curve
- open circuit voltage (Voc)
- short circuit current (Isc)
- peak power
- current and voltage at peak power (Im and Vm)
- fill factor (F.F.)
- Module efficiency (Eff.)
- Module temperature (Temp.)

- 5 Repeatability: +/- 1 +/- 0,5
- 6 Illumination Uniformity: +/- 3% +/- 1 % B-class and AAA-class available

- 7 Test either crystalline or thin films modules and cells

Label printer included with software

Barcode reader for module serial number included

- 10 Dimensions: 1500 x 2500 mm

- 11 Weight: 300 kg

- 12 Measurement range and resolution of voltage: 0.1 - 100V

- 13 Measurement range and resolution of current: 0.1 - 25A

- 14 Measurement range of modules: 40W to 500W

- 15 Yield measurement possible (even for days)

Please ask for more detailed informations if necessary.